



Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 0,5%< E_b ≤ 3%

2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

ECOCERAMIC, S.L.U. Avda. Mediterraneo, 86 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	BS EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Eduardo Caballer (Manager)
Name and function

Onda, 01-01-2021

Place and date of issue





Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 3%< E_b ≤ 6%

2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

ECOCERAMIC, S.L.U. Avda. Mediterraneo, 86 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 000 N	BS EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Eduardo Caballer (Manager)
Name and function

Onda, 01-01-2021

Place and date of issue



1. Unique identification code of the product type Type, batch or serial number or any other element allowing identification of the product Dry-pressed ceramic tiles, with water absorption $E_b > 10 \%$

2. Intended use(s)

For internal wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

ECOCERAMIC, S.L.U.

Avda. Mediterraneo, 86

12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

5. Name and identification number of notified laboratory, if relevant - not applicable Task(s) carried out AVCP system

Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	
Release of dangerous substance, for:		
- Cadmium	NPD	BS EN 14411:2012
- Lead	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	>0,5 N/mm ²	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Eduardo Caballer (Manager) Name and function

Onda, 01-01-2021

Place and date of issue







Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E_b ≤0,5 %

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

ECOCERAMIC, S.L.U. Avda. Mediterraneo, 86 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	BS EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Eduardo Caballer (Manager)
Name and function

Onda, 01-01-2021 Place and date of issue